

Feature

- ① Since the polishing compound necessary for maintaining the polishing performance is uniformly impregnated, so anyone can make easily gloss finish.
- 2 Because the application of polishing compound is unnecessary, the work efficiency gains dramatically.
- 3 Since scattering of polishing compound is small, the work environment is remarkably improved.

Recommended application

- Mirror finish of precious metals and nonferrous metals
- Gloss finishing of iron and stainless steel products

Specifications

• Type of buffs : Loose cloth buff

If you have any requests such as addition of stitches feel free to contact us.

Size

- Outside diameter: 75/100/125/150/200/250/300/350mm
- Thickness: 5 ply(about 5-6mm), 10ply(about 10-12mm)
- Shaft diameter: 9.5, 12.7, 15.9, 19.1, 22.2, 25.4, 38.1mm

Precautions

- To prevent dirt and affix., paper is attached to the buff side. So please remove the paper before using the buff.
- Recommended peripheral speed: 1,000-2,000m/min



KOYO-SHA CO., LTD. http://www.koyo-sha.co.jp

INTERNATIONAL BUSINESS DIV.(TOKYO)

KOYO-SHA BLDG. 9F, NO.48-5, HIGASHI NIPPORI 5-CHOME, ARAKAWA-KU, TOKYO 116-0014 JAPAN TEL: (03)3805-8375 FAX: (03)3805-8369

E-MAIL: obd@koyo-sha.co.jp

HEAD OFFICE/FACTORY(FUKUSHIMA)

NO.1 AZA-SHIOZAWA, TAISHIN NAKASHINJYO SHIRAKAWA-SHI, FUKUSHIMA-KEN 969-0307 JAPAN